

# 1/2" DRIVE IMPACT SOCKET

## DATA SHEET

SIZE RANGE	DRIVE SIZE
10mm - 46mm	1/2"



### PRODUCT OVERVIEW

Built from high-strength steel, this fully hardened and tempered socket is designed for durability and performance in demanding tasks.

Compatible with 1/2" drive impact wrenches and drivers, it delivers high torque and a secure fit, ideal for heavy-duty use.

Whether in automotive, construction, or industrial settings, this socket offers reliable, efficient performance for professionals.

## SPECIFICATIONS

### KEY FEATURES

- Fully Hardened and Tempered – Delivers maximum strength and long-term durability
- 1/2" Drive Size – Suitable for use with impact wrenches and drivers
- High-Strength Steel – Offers excellent wear resistance for extended service life
- Optimised for Heavy-Duty Use

# 1/2" DRIVE IMPACT SOCKET

## DATA SHEET

SPECIFICATIONS	
Shank Type	SDS+
Cutting Edge	4 Tungsten Carbide Cutting Edges
Application	Reinforced Concrete, Masonry

STOCK CODE	SIZE
ISHD10	10mm
ISHD11	11mm
ISHD12	12mm
ISHD13	13mm
ISHD14	14mm
ISHD15	15mm
ISHD16	16mm
ISHD17	17mm
ISHD18	18mm
ISHD19	19mm
ISHD20	20mm
ISHD21	21mm

STOCK CODE	SIZE
ISHD22	22mm
ISHD23	23mm
ISHD24	24mm
ISHD26	26mm
ISHD27	27mm
ISHD28	28mm
ISHD30	30mm
ISHD32	32mm
ISHD34	34mm
ISHD36	36mm
ISHD41	41mm
ISHD46	46mm

## APPLICATIONS

Examples of key applications include:

- Automotive repair and maintenance
- Industrial machinery servicing
- Mechanical assembly and disassembly
- Heavy equipment maintenance

The information provided in this product data sheet is based on the latest available data and is accurate to the best of our knowledge. However, Selkent cannot accept liability for any errors or omissions. The performance and suitability of the product must be evaluated by the end user under their specific conditions and environment. It is the responsibility of the user to ensure compliance with local regulations and safety standards during installation and use. Selkent reserves the right to make changes to product specifications without prior notice