

2 STROKE OIL SHOT 100ML BOTTLE

SAFETY DATA SHEET

MODEL	DESCRIPTION
OIL100	2 Stroke Oil Shot 100ml Bottle



PRODUCT OVERVIEW

Selkent Universal 2 Stroke Oil is a high-quality lubricant designed to deliver outstanding deposit and wear control for air-cooled two-stroke engines. Formulated to meet API TC and JASO FB standards, this oil ensures smooth performance and extended engine life.

Suitable for a wide range of two-stroke applications, including motorcycles, scooters, chainsaws, and other power equipment, it also performs well in water-cooled engines that are not prone to pre-ignition. The 1000ml shot bottle provides convenient, mess-free measuring and easy mixing for both pre-mix and injector systems.

SPECIFICATIONS

KEY FEATURES
• Meets API TC and JASO FB standards
• Reduces engine deposits for cleaner operation
• Provides excellent wear protection for longer engine life
• Suitable for air-cooled and select water-cooled two-stroke engines
• Convenient 1000ml shot bottle for easy use

The information provided in this product data sheet is based on the latest available data and is accurate to the best of our knowledge. However, Selkent cannot accept liability for any errors or omissions. The performance and suitability of the product must be evaluated by the end user under their specific conditions and environment. It is the responsibility of the user to ensure compliance with local regulations and safety standards during installation and use. Selkent reserves the right to make changes to product specifications without prior notice

2 STROKE OIL SHOT 100ML BOTTLE

Compilation date: 20/07/2016

Revision date: 22/02/2022

Revision No: 2

Section 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name: UNIVERSAL TWO STROKE OIL

Product code: A53

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of substance / mixture: Lubricating oil for Two Stroke Engines

1.3. Details of the supplier of the safety data sheet

Company name: Selkent Fastenings Limited

32 Atlas Way

Sheffield

South Yorkshire

S4 7QQ

United Kingdom

Tel: 0114 285 2987

Email: info@penninelubricants.co.uk

1.4. Emergency telephone number

Emergency tel: 0114 285 2987 (Office hours only)

Section 2: Hazards identification

2.1. Classification of the substance or mixture

Classification under CLP: This product has no classification under CLP

2.2. Label elements

Label elements: This product has no label elements.

2.3. Other hazards

PBT: This product is not identified as a PBT/vPvB substance.

Section 3: Composition/information on ingredients

3.2. Mixtures

Hazardous ingredients:

LOW ODOUR KEROSENE - REACH registered number(s): 01-2119456620-43

EINECS	CAS	PBT / WEL	CLP Classification	Percent
926-141-6	-	-	Asp. Tox. 1: H304	1-10%

2 STROKE OIL SHOT 100ML BOTTLE

Section 4: First aid measures

4.1. Description of first aid measures

Skin contact: Wash immediately with plenty of soap and water.

Eye contact: Bathe the eye with running water for 15 minutes.

Ingestion: Wash out mouth with water.

Inhalation: Consult a doctor.

4.2. Most important symptoms and effects, both acute and delayed

Skin contact: There may be mild irritation at the site of contact.

Eye contact: There may be irritation and redness.

Ingestion: There may be irritation of the throat.

Inhalation: No symptoms.

4.3. Indication of any immediate medical attention and special treatment needed

Immediate / special treatment: Not applicable.

Section 5: Fire-fighting measures

5.1. Extinguishing media

Extinguishing media: Carbon dioxide. Alcohol resistant foam. Dry chemical powder.

5.2. Special hazards arising from the substance or mixture

Exposure hazards: In combustion emits toxic fumes.

5.3. Advice for fire-fighters

Advice for fire-fighters: Wear self-contained breathing apparatus. Wear protective clothing to prevent contact with skin and eyes.

Section 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions: Spillages may be slippery. Refer to section 8 of SDS for personal protection details. Turn leaking containers leak-side up to prevent the escape of liquid.

6.2. Environmental precautions

Environmental precautions: Do not discharge into drains or rivers. Contain the spillage using bunding.

6.3. Methods and material for containment and cleaning up

Clean-up procedures: Absorb into dry earth or sand. Transfer to a closable, labelled salvage container for disposal by an appropriate method.

6.4. Reference to other sections

Reference to other sections: Refer to section 8 of SDS.

2 STROKE OIL SHOT 100ML BOTTLE

Section 7: Handling and storage

7.1. Precautions for safe handling

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions: Store in a cool, well-ventilated area. Keep container tightly closed.

7.3. Specific end use(s)

Specific end use(s): No data available.

Section 8: Exposure controls/personal protection

State	Workplace exposure limits:		Workplace exposure limits:	
	8 hour TWA	15min STEL	8 hour TWA	15min STEL
EU	1200mg/m ³	-	-	-

Section 7: Handling and storage

7.1. Precautions for safe handling

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions: Store in a cool, well-ventilated area. Keep container tightly closed.

7.3. Specific end use(s)

Specific end use(s): No data available.

Section 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

State: Liquid

Colour: Red

Odour: Characteristic odour

Evaporation rate: Slow

Solubility in water: Insoluble

Viscosity: Viscous

Kinematic viscosity: 70

Viscosity test method: Kinematic Viscosity at 40°C (cSt)

Boiling point/range°C: >176

Flash point°C: >93

Relative density: 0.88

2 STROKE OIL SHOT 100ML BOTTLE

Section 10: Stability and reactivity

10.1. Reactivity

Reactivity: Stable under recommended transport or storage conditions.

10.2. Chemical stability

Chemical stability: Stable under normal conditions.

10.3. Possibility of hazardous reactions

Hazardous reactions: Hazardous reactions will not occur under normal transport or storage conditions. Decomposition may occur on exposure to conditions or materials listed below.

10.4. Conditions to avoid

Conditions to avoid: Heat.

10.5. Incompatible materials

Materials to avoid: Strong oxidising agents. Strong acids.

10.6. Hazardous decomposition products

Haz. decomp. products: In combustion emits toxic fumes.

Section 11: Toxicological information

11.1. Information on toxicological effects

Hazardous ingredients:
LOW ODOUR KEROSENE

ORAL	RAT	LD50	>5000 mg/kg
------	-----	------	-------------

Toxicity values: No data available

Symptoms / routes of exposure:

Skin contact: There may be mild irritation at the site of contact.

Eye contact: There may be irritation and redness.

Ingestion: There may be irritation of the throat.

Inhalation: No symptoms.

Section 12: Ecological information

12.1. Toxicity

Hazardous ingredients:
LOW ODOUR KEROSENE

RAINBOW TROUT (<i>Oncorhynchus mykiss</i>)	96H LC50	>1000 mg/l
--	----------	------------

2 STROKE OIL SHOT 100ML BOTTLE

12.2. Persistence and degradability

Persistence and degradability: Inherently biodegradable

12.3. Bioaccumulative potential

Bioaccumulative potential: No bioaccumulation potential.

12.4. Mobility in soil

Mobility: Readily absorbed into soil.

12.5. Results of PBT and vPvB assessment

PBT identification: This product is not identified as a PBT/vPvB substance.

12.6. Other adverse effects

Other adverse effects: No data available.

Section 13: Disposal considerations

13.1. Waste treatment methods

Disposal operations: Transfer to a suitable container and arrange for collection by specialised disposal company.

NB: The user's attention is drawn to the possible existence of regional or national regulations regarding disposal.

Section 14: Transport information

Transport class: This product does not require a classification for transport.

Section 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Specific regulations: Not applicable.

15.2. Chemical Safety Assessment

Section 16: Other information

Other information

This safety data sheet is prepared in accordance with Commission Regulation (EU) No 2015/830. Indicates text in the SDS which has changed since the last revision.

Phrases used in s.2 and s.3:

H304: May be fatal if swallowed and enters airways.

Legal disclaimer:

The above information is believed to be correct but does not purport to be all-inclusive and shall be used only as a guide. This company shall not be held liable for any damage resulting from handling or from contact with the above product.